SAFETY DATA SHEET

1. Identification

Product identifier	Talc 80/20
Other means of identification	
Product code	60002
Recommended use	Seed Treatment
Recommended restrictions	Refer to product label.
Manufacturer/Importer/Supplier/I	Distributor information
Manufactured by	TALC USA, LLC.
Address	6100 Industrial Dr.
	Curran, IL 62670
Telephone	800-300-6559
Website	www.talcusa.com
Emergency contact	CHEMTREC (24 Hours):
USA, Canada, Puerto Rico	1-800-424-9300
Virgin Islands	1-800-424-9300
International Maritime	+1 (703) 527-3887

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Acute toxicity, inhalation	Category 4
	Carcinogenicity	Category 1A
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Harmful if inhaled. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Talc (mg3h2(sio3)4) [respirable Dust]		14807-96-6	70 - < 80*
Graphite - All Forms Except Graphite Fibers, Respirable		7782-42-5	10 - < 20*
Other components below report	able levels		1 - < 3
4. First-aid measures			
nhalation	Remove victim to fresh air and keep at rest in artificial respiration if needed. Call a poison co		
Skin contact	Rinse with water. Get medical attention if irrita	ation develops and persists.	
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.		
ngestion	Rinse mouth. Get medical attention if sympton	ms occur.	
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes. Prolonged exposure may cause chronic effects.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and tre under observation. Symptoms may be delaye		m warm. Keep victir
General information	IF exposed or concerned: Get medical advice (show the label where possible). Ensure that involved, and take precautions to protect then	medical personnel are aware	
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carb	on dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as th	is will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be	e formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full p	rotective clothing must be wor	n in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers		
Specific methods	Use standard firefighting procedures and con-	sider the hazards of other invo	olved materials.
General fire hazards	No unusual fire or explosion hazards noted.		
6. Accidental release meas	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep per appropriate protective equipment and clothing NIOSH/MSHA approved respirator if there is the exposure limits. Ensure adequate ventilat spillages cannot be contained. For personal p	during clean-up. Do not brea a risk of exposure to dust/fum ion. Local authorities should b	athe dust. Use a e at levels exceeding be advised if significa

Methods and materials for
containment and cleaning upAvoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust
using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Avoid discharge into drains, water courses or onto the ground.

Store in secured area away from children, feed, and other food products. Store in original container. Store in a well-ventilated area. Storage temperature: 40 F to 100 F.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFF Components	R 1910.1000) Type	Value	Form
Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5)	TWA	15 mppcf	
Talc (mg3h2(sio3)4) [respirable Dust] (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit			_
Components	Туре	Value	Form
Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Talc (mg3h2(sio3)4)	TWA	2 mg/m3	Respirable fraction.
[respirable Dust] (CAS 14807-96-6)			
[respirable Dust] (CAS	Chemical Hazards		
[respirable Dust] (CAS 14807-96-6)	Chemical Hazards Type	Value	Form
[respirable Dust] (CAS 14807-96-6) US. NIOSH: Pocket Guide to		Value 2.5 mg/m3	Form Respirable.
[respirable Dust] (CAS 14807-96-6) US. NIOSH: Pocket Guide to Components Graphite - All Forms Except Graphite Fibers, Respirable	Туре		-
[respirable Dust] (CAS 14807-96-6) US. NIOSH: Pocket Guide to Components Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5) Talc (mg3h2(sio3)4) [respirable Dust] (CAS	Type TWA	2.5 mg/m3 2 mg/m3	Respirable.
[respirable Dust] (CAS 14807-96-6) US. NIOSH: Pocket Guide to Components Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5) Talc (mg3h2(sio3)4) [respirable Dust] (CAS 14807-96-6)	Type TWA TWA	2.5 mg/m3 2 mg/m3 e ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If exp n acceptable level. If engin st particulates below the C st be worn. If material is gro	Respirable. Respirable. e matched to conditions. If er engineering controls to posure limits have not been eering measures are not occupational Exposure Limit pund, cut, or used in any
[respirable Dust] (CAS 14807-96-6) US. NIOSH: Pocket Guide to Components Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5) Talc (mg3h2(sio3)4) [respirable Dust] (CAS 14807-96-6) logical limit values propriate engineering trols	Type TWA TWA No biological exposure limits noted for the Good general ventilation should be used. applicable, use process enclosures, local maintain airborne levels below recommen established, maintain airborne levels to ar sufficient to maintain concentrations of du (OEL), suitable respiratory protection mus operation which may generate dusts, use below the recommended exposure limits. such as personal protective equipment	2.5 mg/m3 2 mg/m3 e ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If exp n acceptable level. If engin st particulates below the C to be worn. If material is gro appropriate local exhaust	Respirable. Respirable. e matched to conditions. If er engineering controls to bosure limits have not been eering measures are not Occupational Exposure Limit bund, cut, or used in any ventilation to keep exposure
[respirable Dust] (CAS 14807-96-6) US. NIOSH: Pocket Guide to Components Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5) Talc (mg3h2(sio3)4) [respirable Dust] (CAS 14807-96-6) logical limit values propriate engineering trols	Type TWA TWA No biological exposure limits noted for the Good general ventilation should be used. applicable, use process enclosures, local maintain airborne levels below recommen established, maintain airborne levels to ar sufficient to maintain concentrations of du (OEL), suitable respiratory protection mus operation which may generate dusts, use below the recommended exposure limits.	2.5 mg/m3 2 mg/m3 e ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If exp n acceptable level. If engin st particulates below the C to be worn. If material is gro appropriate local exhaust	Respirable. Respirable. e matched to conditions. If er engineering controls to bosure limits have not been eering measures are not Docupational Exposure Limit bund, cut, or used in any ventilation to keep exposure
[respirable Dust] (CAS 14807-96-6) US. NIOSH: Pocket Guide to Components Graphite - All Forms Except Graphite Fibers, Respirable (CAS 7782-42-5) Talc (mg3h2(sio3)4) [respirable Dust] (CAS 14807-96-6) logical limit values propriate engineering trols	Type TWA TWA No biological exposure limits noted for the Good general ventilation should be used. applicable, use process enclosures, local maintain airborne levels below recommen established, maintain airborne levels to ar sufficient to maintain concentrations of du (OEL), suitable respiratory protection mus operation which may generate dusts, use below the recommended exposure limits. such as personal protective equipment	2.5 mg/m3 2 mg/m3 e ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If exp n acceptable level. If engin st particulates below the C st be worn. If material is gr appropriate local exhaust rtridge, full facepiece, dus	Respirable. Respirable. e matched to conditions. If er engineering controls to bosure limits have not been eering measures are not Occupational Exposure Limit bund, cut, or used in any ventilation to keep exposure

Respiratory protection	Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

, ,	•
Appearance	
Physical state	Solid.
Form	Powder.
Color	Light grey
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling	6587.6 °F (3642 °C) estimated
range	
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	124256.1 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	845.6 °F (452 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	2.66 g/cm3 estimated
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	2.67 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Chlorine.

11. Toxicological information

Information on likely routes of exposure			
Inhalation	Harmful if inhaled.		
Skin contact	Dust or powder may irritate the skin.		
Eye contact	Dust may irritate the eyes.		
Ingestion	Knowledge about health hazard is incomplete.		
Symptoms related to the physical, chemical and toxicological characteristics	Dusts may irritate the respiratory tract, skin and eyes.		

Information on toxicological effects

Acute toxicity	Harmful if inhaled.	
Product	Species	Test Results
Talc 80/20		
<u>Acute</u>		
Oral		
LD50	Rat	51280 mg/kg
Components	Species	Test Results
Graphite - All Forms Except Graph	ite Fibers, Respirable (CAS 77	82-42-5)
Acute		
Oral		
LD50	Rat	> 10000 mg/kg
Skin corrosion/irritation		k of data the classification is not possible.
Serious eye damage/eye irritation	Due to partial or complete lac	k of data the classification is not possible.
Respiratory or skin sensitizatior	ı	
Respiratory sensitization	Due to partial or complete lac	k of data the classification is not possible.
Skin sensitization	Due to partial or complete lac	k of data the classification is not possible.
Germ cell mutagenicity	Due to partial or complete lac	k of data the classification is not possible.
Carcinogenicity	May cause cancer.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity	
Talc (mg3h2(sio3)4) [resp	birable Dust] (CAS 14807-96-6)	2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.
	d Substances (29 CFR 1910.1	001-1053)
Not listed. US. National Toxicology Pro	ogram (NTP) Report on Carcir	logens
Not listed.		•
Reproductive toxicity	Due to partial or complete lac	k of data the classification is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lac	k of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Causes damage to organs th	rough prolonged or repeated exposure.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.	
Chronic effects	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.	
12. Ecological information		-
Ecotoxicity		as environmentally hazardous. However, this does not exclude the not spills can have a harmful or damaging effect on the environment.
Persistence and degradability		egradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	

Material name: Talc 80/20

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard	Acute toxicity (any route of exposure)
categories	Carcinogenicity
	Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65

WARNING: This product can expose you to chemicals including arsenic, cadmium, and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Talc (mg3h2(sio3)4) [respirable Dust] (CAS 14807-96-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	08-19-2022
Revision date	06-03-2024
Version #	04
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of Manufacturer's knowledge, information and belief at the date of its publication; however, it is provided only as a guidance for safe handling, use, processing, storage, transportation, disposal and release of the Product. No warranties of any kind, either expressed or implied, including warranties of merchantability or fitness for a particular purpose, are made with respect to the Product or the information provided herein, or that the Product or information provided in this Safety Data Sheet relates only to the specific Product designated and may not be valid if the Product is used in combination with other materials or in any other process, unless specified herein. The user assumes all risk and liability for loss, injury, damage or expense due to any use, handling, storage or disposal of the Product, and Manufacturer recommends that the user conducts its owns tests of the Product to determine suitability of the Product for user's particular use.